

Serial No. 09/750,051

IN THE CLAIMS:

The text of all pending claims, (including withdrawn claims) is set forth below. Cancelled and not entered claims are indicated with claim number and status only. The claims as listed below show added text with underlining and deleted text with ~~striketrough~~. The status of each claim is indicated with one of (original), (currently amended), (cancelled), (withdrawn), (new), (previously presented), or (not entered).

Please AMEND claims 1-9, 14-16, and 19-22 in accordance with the following:

1. (CURRENTLY AMENDED) A noise countermeasure determination method comprising ~~the steps of~~:
 - (a) calculating recommended circuit information considered to minimize a noise by use of at least one formula, based on input circuit information amounting to at least one net of a target circuit which is to be subjected to a noise analysis; and
 - (b) comparing the input circuit information and the recommended circuit information, and determining a differing portion of the recommended circuit information differing from the input circuit information, as noise countermeasures.
2. (CURRENTLY AMENDED) The noise countermeasure determination method as claimed in claim 1, further comprising ~~the steps of~~:
 - (c) creating a simulation model of the input circuit information after determining the noise countermeasures ~~in said step (b)~~;
 - (d) carrying out a circuit simulation using the simulation model, to calculate a signal waveform propagating through a wiring of the target circuit and to check whether or not a noise exceeding a tolerable range exists in the signal waveform; and
 - (e) categorizing the noise existing as a result of the noise check ~~carried out in said step (d)~~, and optimizing the determined noise countermeasures to only portions related to the noise.
3. (CURRENTLY AMENDED) The noise countermeasure determination method as claimed in claim 1, wherein ~~said step (a)~~ the calculating recommended circuit information comprises outputting outputs a range of a damping resistance as the recommended circuit information, based on a minimum voltage VIH-1 and a maximum voltage VIH-2 which guarantee a normal operation of the target circuit, by taking a damping resistance which makes a first rising voltage of an input waveform at a receiving end of the target circuit equal to the minimum

Serial No. 09/750,051

voltage VIH-1 as a maximum value of the range, and taking a damping resistance which makes the first rising voltage of the input waveform at the receiving end of the target circuit equal to the maximum voltage VIH-2 as a minimum value of the range.

4. (CURRENTLY AMENDED) The noise countermeasure determination method as claimed in claim 3, wherein ~~said step (a)~~ the calculating recommended circuit information comprises:

~~compares~~ comparing a damping resistance which makes a voltage at a time of a ringback equal to the minimum voltage VIH-1 and the minimum value of the damping resistance, and

~~outputs~~ outputting a larger one of the compared values as the minimum value of the damping resistance.

5. (CURRENTLY AMENDED) The noise countermeasure determination method as claimed in claim 1, further comprising ~~the step of: (e) outputting input circuit information which that includes as:~~ a wiring length; that is substantially a Manhattan distance which that is determined based on positions of part pins forming the target circuit and a wiring topology.

6. (CURRENTLY AMENDED) The noise countermeasure determination method as claimed in claim 5, further comprising ~~the steps of:~~

~~(d) creating a simulation model of the input circuit information after determining the noise countermeasures in said step (b);~~

~~(e) carrying out a circuit simulation using the simulation model, to calculate a signal waveform propagating through a wiring of the target circuit and to check whether or not a noise exceeding a tolerable range exists in the signal waveform; and~~

~~(f) repeating said step (d) and said step (e)~~ the creating a simulation model and the carrying out a circuit simulation using the simulation model using a plurality of wiring topologies, and determining an optimum wiring topology from results of the noise check carried out in said step (e) carrying out a circuit simulation using the simulation model to for use in said step (e), outputting input circuit information so that the optimum wiring topology is determined as the noise countermeasures in said step (b) comparing the input circuit information and the recommended circuit information.

7. (CURRENTLY AMENDED) The noise countermeasure determination method as

Serial No. 09/750,051

claimed in claim 1, further comprising ~~the steps of:~~

(e) creating a simulation model of input circuit information made up of circuit information of a target net which is to be subjected to the noise analysis and circuit information of an adjacent net which is adjacent to the target net, after determining the noise countermeasures in ~~said step (b);~~

(d) carrying out a circuit simulation using the simulation model, to obtain a noise combined waveform by combining a crosstalk noise waveform and a signal waveform propagating through the target net which are calculated, and to check whether or not a noise exceeding a tolerable range exists based on the noise combined waveform; and

(e) categorizing the noise existing as a result of the noise check ~~carried out in said step (d)~~, and optimizing the determined noise countermeasures to only portions related to the noise.

8. (CURRENTLY AMENDED) The noise countermeasure determination method as claimed in claim 7, wherein said ~~step (e)~~ creating a simulation model creates the simulation model by assuming that the circuit information of the adjacent net is related to a net which has the same structure as the target net and is adjacent to the target net with a constant pattern gap formed therebetween.

9. (CURRENTLY AMENDED) The noise countermeasure determination method as claimed in claim 8, wherein said ~~step (e)~~ creating a simulation model and said ~~step (d)~~ carrying out a circuit simulation using the simulation model are repeated while changing the pattern gap, so as to obtain a minimum pattern gap with which the noise obtained as a result of the noise check carried out in said ~~step (d)~~ carrying out a circuit simulation using the simulation model does not exceed the tolerable range, and said ~~step (b)~~ comparing the input circuit information and the recommended circuit information determines the minimum pattern gap as the noise countermeasures.

10. (ORIGINAL) A noise countermeasure determination apparatus comprising:
a recommended circuit information calculating section calculating recommended circuit information considered to minimize a noise by use of at least one formula, based on input circuit information amounting to at least one net of a target circuit which is to be subjected to a noise analysis; and
a noise countermeasure determination section comparing the input circuit information and the recommended circuit information, and determining a differing portion of the

Serial No. 09/750,051

recommended circuit information differing from the input circuit information, as noise countermeasures.

11. (ORIGINAL) The noise countermeasure determination apparatus as claimed in claim 10, further comprising:

a circuit model creating section creating a simulation model of the input circuit information after determining the noise countermeasures in said noise countermeasure determination section;

a simulation and check section carrying out a circuit simulation using the simulation model, to calculate a signal waveform propagating through a wiring of the target circuit and to check whether or not a noise exceeding a tolerable range exists in the signal waveform; and a noise countermeasure optimizing section categorizing the noise existing as a result of the noise check carried out in said simulation and check section, and optimizing the determined noise countermeasures to only portions related to the noise.

12. (ORIGINAL) The noise countermeasure determination apparatus as claimed in claim 10, wherein said recommended circuit information calculating section outputs a range of a damping resistance as the recommended circuit information, based on a minimum voltage VIH-1 and a maximum voltage VIH-2 which guarantee a normal operation of the target circuit, by taking a damping resistance which makes a first rising voltage of an input waveform at a receiving end of the target circuit equal to the minimum voltage VIH-1 as a maximum value of the range, and taking a damping resistance which makes the first rising voltage of the input waveform at the receiving end of the target circuit equal to the maximum voltage VIH-2 as a minimum value of the range.

13. (ORIGINAL) The noise countermeasure determination apparatus as claimed in claim 12, wherein said recommended circuit information calculating section compares a damping resistance which makes a voltage at a time of a ringback equal to the minimum voltage VIH-1 and the minimum value of the damping resistance, and outputs a larger one of the compared values as the minimum value of the damping resistance.

14. (CURRENTLY AMENDED) The noise countermeasure determination apparatus as claimed in claim 10, further comprising:

a circuit information output section outputting input circuit information ~~which~~ that includes

Serial No. 09/750,051

as a wiring length; that is substantially a Manhattan distance ~~which that~~ is determined based on positions of part pins forming the target circuit and a wiring topology.

15. (CURRENTLY AMENDED) The noise countermeasure determination apparatus as claimed in claim 13, further comprising:

a circuit model creating section creating a simulation model of the input circuit information after determining the noise countermeasures in said noise countermeasure determination section; and

a simulation and check section carrying out a circuit simulation using the simulation model, to calculate a signal waveform propagating through a wiring of the target circuit and to check whether or not a noise exceeding a tolerable range exists in the signal waveform; ~~and~~

wherein processes of said circuit model creating section and said simulation and check section being repeated using a plurality of wiring topologies, and an optimum wiring topology being determined from results of the noise check carried out by said simulation and check section for use by said circuit model creating section, so that the optimum wiring topology is determined as the noise countermeasures by said noise countermeasure determination section.

16. (ORIGINAL) The noise countermeasure determination apparatus as claimed in claim 10, further comprising:

a circuit model creating section creating a simulation model of input circuit information made up of circuit information of a target net which is to be subjected to the noise analysis and circuit information of an adjacent net which is adjacent to the target net, after determining the noise countermeasures by said noise countermeasure determination section;

a simulation and check section carrying out a circuit simulation using the simulation model, to obtain a noise combined waveform by combining a crosstalk noise waveform and a signal waveform propagating through the target net which are calculated, and to check whether or not a noise exceeding a tolerable range exists based on the noise combined waveform; and

a noise countermeasure optimizing section categorizing the noise existing as a result of the noise check carried out by said simulation and check section, and optimizing the determined noise countermeasures to only portions related to the noise.

17. (ORIGINAL) The noise countermeasure determination apparatus as claimed in claim 16, wherein said circuit model creating section creates the simulation model by assuming that the circuit information of the adjacent net is related to a net which has the same structure

Serial No. 09/750,051

as the target net and is adjacent to the target net with a constant pattern gap formed therebetween.

18. (ORIGINAL) The noise countermeasure determination apparatus as claimed in claim 17,

wherein processes of said circuit model creating section and said simulation and check section are repeated while changing the pattern gap, so as to obtain a minimum pattern gap with which the noise obtained as a result of the noise check carried out by said simulation and check section does not exceed the tolerable range, and said noise countermeasure determination section determines the minimum pattern gap as the noise countermeasures.

19. (CURRENTLY AMENDED) A computer-readable storage medium which stores storing a program for ~~causing~~ controlling a computer to determine noise countermeasures, said program comprising by:

~~a recommended circuit information calculating procedure causing the computer to calculate~~ calculating recommended circuit information considered to minimize a noise by use of at least one formula, based on input circuit information amounting to at least one net of a target circuit which is to be subjected to a noise analysis; and

~~a noise countermeasure determination procedure causing the computer to compare~~ comparing the input circuit information and the recommended circuit information, ~~and to~~ and ~~determine~~ determining a differing portion of the recommended circuit information differing from the input circuit information, as noise countermeasures.

20. (CURRENTLY AMENDED) The noise countermeasure determination method as claimed in claim 1, further comprising ~~the step of: (e)~~ carrying out at least one of a circuit rule check and a wiring topology check with respect to the input circuit information.

21. (CURRENTLY AMENDED) The noise countermeasure determination method as claimed in claim 20, further comprising ~~the step of: (d)~~ outputting an advice based on a check result obtained in ~~said step (e)~~.

22. (CURRENTLY AMENDED) The noise countermeasure determination method as claimed in claim 21, further comprising ~~the step of: (e)~~ correcting the input circuit information based on the advice output in ~~said step (d)~~.